



DECLARATION OF PERFORMANCE

In accordance with EU Construction Products Regulation (CPR) no 305/2011

No: 1121-CPR-BB5005

1. Unique identification of the product-type:

Essgee Fireply (Type D1) ATP FR Euro Class B: 9mm to 25mm

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Malayan / Chinese Plywood 2440x1220 (9, 12, 15, 18, 22, 25)mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Wood Based Panel for internal use as a non-structural component in dry conditions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

Saint-Gobain Building Distribution Ltd (Trading as International Timber) West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ +44(0)161 848 2906

www.internationaltimber.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Warrington Certification Ltd (1121)

performed:

Initial and continuous surveillance of the place of manufacture and the factory production control implemented, sampled product and witnessed initial type testing under system

1

and issued:

The Certificate of Constancy of Performance No. 1121-CPR-BB5005

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire, Euroclass characteristics	Class B-s2,d0	EN 13986:2004
Durability against aging (Bending Test)	NPD	
Bonding Quality	NPD	
Internal bond (Tensile Strength)	NPD	
Release of Formaldehyde	E1	EN 13986:2004 Annex B Note 2
Water Vapour Permeability	NPD	
Airborne Sound Insulation	NPD	
Sound Absorption	NPD	
Thermal Conductivity	NPD	
Biological Durability	NPD	
Content of Pentachlorophenol	NPD	

9. Where pursuant to Article 37 or 38, the Specific Technical Documentation that has been used, the requirements with which the product complies:

Classification Report No. 139863

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Clare Pickin

Operations Director

Che Pula

Manchester

December 2017

CE

1121-CPR-BB5005

Saint-Gobain Building Distribution Ltd (T/A International Timber) www.internationaltimber.com

14 BS EN 13986:2004 BS EN 13501-1

E1

Hardwood Plywood

Thickness: 9mm – 25mm

Reaction to Fire Class B-s2,d0

For non-structural use in dry conditions without