

Notified body No. 1121

Certificate of constancy of performance

1121-CPR-BB5006

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

“Birch Plywood Dricon™ FR Euro Class B: 12mm to 25mm”

Intended use: **Wood Based Panels**

Product Performance

Essential characteristics	Performance	Harmonized technical specification
Safety in case of Fire, Reaction to fire	B-S ₁ -d ₀	EN 13986:2004 (Classification report No: 184309)

Product Specification (See Page 3)

Certificate of constancy of performance

1121-CPR-BB5006

Produced for

International Timber

West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ

and produced in the manufacturing plant(s)

West Yard, Trafford Wharf Road, Trafford Park, Manchester M17 1DJ
London Road, Purfleet, Essex, RM19 1RE
Earls Road, Grangemouth, Stirlingshire, FK3 8UU

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 13986:2004

under system 1 of AVCP are applied and that

the product fulfils all the prescribed requirements set out above.

This certificate was first issued on **19/05/14** and revised on **10/9/18** and will remain valid to the date given below as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Valid to: **9/9/21**



Paul Duggan
Certification Manager

Exova (UK) Limited trading as Warrington Certification
Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK



Certificate of constancy of performance

1121-CPR-BB5006

Product Specification

General description	Fire retardant birch ply
Trade name	Birch Plywood Dricon™ FR Euro Class B: 12mm to 25mm
Thickness	12mm-25mm
Density	670kg/m3
Flame retardant trade name	Dricon
Net chemical retention	See Note 1 below
Cycle details	See Note 1 below
Brief description of manufacturing process	Pressure impregnation

Note 1: The sponsor of the test has provided this information but at the specific request of the sponsor, this information has been omitted from the test report and is instead held on the confidential file relating to this investigation.

----- End of Certificate -----