

# FIBRAPAN HIDROFUGO

by **FINSA**

The bar has been raised  
with the highest standard in **quality.**

## Excellent machining quality

Our unique manufacturing process ensures a stronger consistent bond in the core, for a clean cut and perfect for routing.



@blucarpentry



@freebirdinteriors

## Superior paint finish

Obtain a better finish with less work. A denser board that requires less preparation time and less paint giving you an optimal finish.

## Moisture Resistant MDF

Enhanced performance during cyclic test (EN 321, V313), with great results in both thickness swelling and internal bond.

### Technical Data

UK STOCK
2440 x 1220
06 mm 09 mm
18 mm 22 mm
25 mm 30 mm

Properties	Units	Thickness mm				
		>4/6	>6/9	>9/12	>12/19	>19/30
DENSITY (*)	kg/m <sup>3</sup>	855/830	825/770	765/745	745/730	730/715
INTERNAL BOND	N/mm <sup>2</sup>	0.85	0.80	0.80	0.75	0.75
BENDING STRENGTH	N/mm <sup>2</sup>	27	27	26	24	22
MODULUS OF ELASTICITY	N/mm <sup>2</sup>	2700	2700	2500	2400	2300

\*E1 classification: low formaldehyde content.

**CLICK TO WATCH WHAT CUSTOMERS SAY ABOUT IT**



@freebirdinteriors



@greenwichalcoveco



Get in touch to find your nearest stockist  
T: 0151 651 2400 E: uk@finsa.com IG: @finsauk



**FINSA**