

European Prime Beech

BOTANICAL NAME

Fagus sylvatita

Further Product Information

APPLICATIONS & USES

Quality Joinery Manufacturing, Furniture, Mouldings, Door Frames, Flooring, Staircases

DIMENSIONS

Prime S/E Steamed Beech (Prime Square Edged European Beech)

- 26mm
- 32mm
- 38mm
- 50mm
- 65mm
- 80mm

Prime S/e Steamed Beech Pol 2.45m

- 26mm Sanded (23.8mm)
- 32mm Sanded (29.5mm
- 38mm Sanded (36.0mm)
- 52mm Sanded (48.5mm)
- 64mm Sanded (60.5mm)

Prime S/e Steamed Beech Pol 3.05m

- 26mm Sanded (23.8mm)
- 32mm Sanded (29.5mm)
- 38mm Sanded (36.0mm)
- 52mm Sanded (48.5mm)
- 64mm Sanded (60.5mm)

Prime S/e Steamed Beech Pol 3.35m

- 26mm Sanded (23.8mm)
- 32mm Sanded (29.5mm)



38mm Sanded (36.0mm)	
---------------------------------	---------	--

- 52mm Sanded (48.5mm)
- 64mm Sanded (60.5mm)

Prime S/e White Beech K/d

- 26mm
- 32mm
- 38mm
- 50mm

ENVIRONMENTAL CREDENTIALS

Certification

FSC

PEFC

Origin

France, Germany, Croatia, Romania

TECHNICAL INFORMATION

Density

720kg/m3

Physical Structure

Clear 1 face and better, allowing minor defects and very occasional colour on reverse

Durability

Non Durable (Good Fire Rating)

Drying

Χ

Moisture Content

13% Average

Working Qualities

Χ

Glue Line



Χ

Supplied Finish

Rough Sawn

Storage Advice

Under cover

Wastage Allowance

40% Recommended