

Hidrofugo

BOTANICAL NAME

**Picea abies (spruce) / Pinus
sylvestris (pine)**



OVERVIEW

Our Hidrofugo moisture resistant MDF panel offering is designed for use in humid conditions.

It has excellent machining quality that ensures a stronger consistent bond in the core, allowing a clean cut that is perfect for routing. The denser board requires less preparation time, less paint which gives a superior paint finish.

Further Product Information

APPLICATIONS & USES

Shopfitting, general purpose joinery, exhibition and furniture

DIMENSIONS

Hidrofugo 2440 x 1220 (MDF Moisture Resistant)

- 6mm
- 9mm
- 12mm
- 18mm
- 22mm

– 25mm

Hidrofugo 3050 x 1220 (MDF Moisture Resistant)

– 9mm

– 12mm

– 18mm

– 22mm

ENVIRONMENTAL CREDENTIALS

Certification

FSC®

Origin

Norbord: Scotland, Medite: Ireland, Finsa: Spain

TECHNICAL INFORMATION

Physical Structure

EN321, V313

Storage Advice

Transport in uniform stacks on a flat base to avoid damage. Protect against the weather; store on a rigid flat base and adequately ventilated. Insulate from the ground to avoid dampness. When wooden battens are used they shall be of uniform thickness and placed in line. The distance between the battens should be no greater than 700 – 1000mm

Purchasing Cycle

Weekly