

## Tricoya MDF

### BOTANICAL NAME

**Picea abies (Spruce) / Pinus  
sylvestris(Pine) / Pinus radiata**



### OVERVIEW

**MEDITE TRICOYA EXTREME (MTX)** is an extremely durable MDF that offers outstanding dimensional stability and comes with a 50 year guarantee.

Exterior MDF is used as a substitute for softwood, hardwood, plywood, plastic and metal in non-stressed applications.

For an MTX Brochure please [click here](#).click here.

## Further Product Information

### APPLICATIONS & USES

Exterior facades and cladding as well as door and sign manufacture.

### DIMENSIONS

**Medite Tricoya 2440 x 1220 (Special MDF)**

- 6mm
- 9mm
- 12mm
- 15mm
- 18mm

**Medite Tricoya 3050 x 1220 (Special MDF)**

- 18mm
- 15mm

**Exterior Grade 2440 x 1220 (Special MDF)**

- 15mm
- 12mm
- 9mm
- 6mm

**Tricoya 2440 x 1220 (MDF Moisture Resistant)**

- 6mm
- 9mm
- 12mm
- 15mm
- 18mm

**Tricoya 3050 x 1220 (MDF Moisture Resistant)**

- 15mm
- 18mm

**ENVIRONMENTAL CREDENTIALS**

**Certification**

FSC® Certified

**Origin**

Ireland

**TECHNICAL INFORMATION**

**Physical Structure**

EN 622-5 ; BS EN 120(E1)

**Storage Advice**

Transport in uniform stacks on a flat base to avoid damage. Protect against the weather, store on a rigid flat base and adequately ventilated. Insulate from the ground to avoid dampness. When wooden battens are used they shall be of uniform thickness and placed in line. The distance between the battens should be no greater than 700-1000mm

### **Purchasing Cycle**

Monthly