Tricoya MDF

BOTANICAL NAME

Picea abies (Spruce) / Pinus sylvestris(Pine) / Pinus radiata

OVERVIEW

MEDITE TRICOYA EXTREME (MTX) is an extremely durable MDF that offers outstanding dimensional stability and comes with a 50 year guarantee.

Exterior MDF is used as a substitute for softwood, hardwood, plywood, plastic and metal in non-stressed applications.

For an MTX Brochure please click here.click here.

Further Product Information

APPLICATIONS & USES

Exterior facades and cladding as well as door and sign manufacture.

DIMENSIONS

© International Timber 2026

Medite Tricoya 2440 x 1220 (Special MDF)

– 6mm
– 9mm
– 12mm
– 15mm
– 18mm

Medite Tricoya 3050 x 1220 (Special MDF)

– 18mm
– 15mm

Exterior Grade 2440 x 1220 (Special MDF)

– 15mm
– 12mm
– 9mm
– 6mm

Tricoya 2440 x 1220 (MDF Moisture Resistant)

– 6mm
– 9mm
– 12mm
– 15mm
– 18mm

Tricoya 3050 x 1220 (MDF Moisture Resistant)

– 15mm
– 18mm

ENVIRONMENTAL CREDENTIALS

Certification

FSC&® Certified

Origin

Ireland

TECHNICAL INFORMATION

Physical Structure

EN 622-5 ; BS EN 120(E1)

Storage Advice

Transport in uniform stacks on a flat base to avoid damage. Protect against the weather, store on a rigid flat base and adequately ventilated. Insulate from the ground to avoid dampness. When wooden battens are used they shall be of uniform thickness and placed in line. The distance between the battens should be no greater than 700-1000mm

Purchasing Cycle
Monthly

© International Timber 2026