

# **Tricoya MDF**

**BOTANICAL NAME** 

Picea abies (Spruce) / Pinus sylvestris(Pine) / Pinus radiata



**OVERVIEW** 

**MEDITE TRICOYA EXTREME (MTX)** is an extremely durable MDF that offers outstanding dimensional stability and comes with a 50 year guarantee.

Exterior MDF is used as a substitute for softwood, hardwood, plywood, plastic and metal in non-stressed applications.

For an MTX Brochure please click here.click here.

### **Further Product Information**

**APPLICATIONS & USES** 

Exterior facades and cladding as well as door and sign manufacture.

**DIMENSIONS** 



Medite Tricoya 2440 x 1220 (Special MDF)  - 6mm  - 9mm  - 12mm  - 15mm  - 18mm
Medite Tricoya 3050 x 1220 (Special MDF)  – 18mm  – 15mm
Exterior Grade 2440 x 1220 (Special MDF)  - 15mm  - 12mm  - 9mm  - 6mm
Tricoya 2440 x 1220 (MDF Moisture Resistant)  - 6mm  - 9mm  - 12mm  - 15mm  - 18mm
Tricoya 3050 x 1220 (MDF Moisture Resistant) – 15mm – 18mm
ENVIRONMENTAL CREDENTIALS
Certification FSC&® Certified
Origin

#### **TECHNICAL INFORMATION**

## **Physical Structure**

Ireland

EN 622-5; BS EN 120(E1)

### **Storage Advice**



Transport in uniform stacks on a flat base to avoid damage. Protect against the weather, store on a rigid flat base and adequately ventilated. Insulate from the ground to avoid dampness. When wooden battens are used they shall be of uniform thickness and placed in line. The distance between the battens should be no greater than 700-1000mm

**Purchasing Cycle** 

Monthly