

European Oak Laminated Window Sections



Further Product Information

DIMENSIONS

Sash Casement (European Oak Laminated)

- 64 x 86mm x 2.4m
- 64 x 76mm x 2.4m
- 64 x 86mm x 2.4m
- 64 x 96mm x 2.4m
- 74 x 58mm x 2.4m
- 64 x 76mm x 2.4m
- 64 x 86mm x 2.4m
- 64 x 96mm x 2.4m
- 74 x 58mm x 2.4m

Frame (European Oak Laminated)

- 105mm x 76mm x 2.4m
- 105mm x 85mm x 2.4m
- 110mm x 85mm x 2.4m

ENVIRONMENTAL CREDENTIALS

Certification

FSC

Or non certified

TECHNICAL INFORMATION

Grade

Colour matches, small sound knots, no wane or sap on faces or edges. Saps allowed to a maximum one third of one edge only. Defects can be placed in the «hidden nonvisible» lamellas of a

distance of 12mm from all surfaces.

Moisture Content

14% +/- 2%

Length

1.0m / 3.0m

Glue Line

PVAC, D4

Joint Distance Finger Joints

Outer faces are solid, centre lamellas can be finger jointed to a maximum of 3 per length

Dimensional Tolerance

Max 0.5mm deviated on thickness/width

Lamella Thickness

0.5mm deviation, as long as total thickness conforms

Bow/Twist/Bend

1mm per lineal metre

Construction

200mm boards will be one piece in width no joint