

Sapele Laminated Window Sections



OVERVIEW

Sapele DKD core range no finger joints on outer faces.

Further Product Information

DIMENSIONS

Sash Casement (Sapele Laminated)

- 64 x 76mm x 2.4m
- 64 x 96mm x 2.4m
- 74 x 58mm x 2.4m
- 64 x 86mm x 2.4m
- 64 x 76mm x 2.4m
- 64 x 86mm x 2.4m
- 64 x 96mm x 2.4m
- 74 x 58mm x 2.4m
- 64 x 76mm x 2.4m
- 64 x 86mm x 2.4m
- 64 x 96mm x 2.4m
- 74 x 58mm x 2.4m

Frame (Sapele Laminated)

- 110 x 85mm x 2.4m
- 105 x 85mm x 2.4
- 105 x 76mm x 2.4m

ENVIRONMENTAL CREDENTIALS

Certification

FSC

3rd Party Legality COC

TECHNICAL INFORMATION

Moisture Content

12% +/- 2%

Grade

First & seconds “ No SAP on faces or edges, colour matched. No knots, wane or splits. Defects can be placed in the hidden nonvisible lamellas at a distance of 12mm from all surfaces. Max number of finger joints on centre lamellas can be 7.

Length

0.9m / 3.0m

Glue Line

PVAC, D4

Construction

Minimum distance between joints 150mm on face.