

Accoya Laminated Window Sections

Further Product Information



DIMENSIONS

Sash (Accoya® Laminated)

- 75 x 63mm x 6m 3 Ply x 25 x 63
- 72 x 63mm x 6m 3 Ply x 24 x 63
- 63 x 61mm x 6m 3 Ply x 21 x 61

Sash Casement (Accoya® Laminated)

- 63 x 72mm x 6m 3 Ply x 21 x 72

Frame (Accoya® Laminated)

- 63 x 100mm x 6m 3 Ply x 21 x 100
- 96 x 61mm x 6m 3 Ply x 24 x 61
- 96 x 72mm x 6m 4 Ply x 24 x 72
- 110 x 63mm x 6m 5 Ply x 22 x 63
- 110 x 75mm x 6m 5 Ply x 22 x 75

ENVIRONMENTAL CREDENTIALS

Certification

FSC
PEFC

TECHNICAL INFORMATION

Grade

Four sides clear (knot and defect free). Defects can be placed in the hidden 'non visible' lamellas of a distance of min 12mm from all surfaces vertical/semi vertical grain on all face lamellas Standard on sections up to 98mm face.

Moisture Content

12% +/- 2%

Length

6.0m

Glue Line

PVAC, D4

Joint Distance Finger Joints

150 – 900mm

Dimension Tolerance

Max 0.5mm deviated on thickness/width

Lamella Thickness

0.5mm deviation, as long as total thickness conforms

Bow/Twist/Bend

1mm per lineal metre