

European Redwood Decking

BOTANICAL NAME

Pinus sylvestris



OVERVIEW

Available Grades:-

5th Grade

Live sound knots, no wane, no blue stain

Reversible Decking

Further Product Information

APPLICATIONS & USES

Joinery – windows and doors, decking, cladding, construction

DIMENSIONS

Deck Boards (Softwood Decking)

- 26 x 117mm Reversible
- 32 X 117mm Reversible
- 28 x 145mm Reversible

Rails (Softwood Decking)

- 34 x 78mm x 2.4m to 5.4m Patterned Handrail
- 34 x 78mm x 2.4m to 5.4m Patterned Handrail
- 32 x 78mm x 2.4m to 5.4m Baserail
- 12 x 42mm x 2.4m to 5.1m Fillet

Posts (Softwood Decking)

- 95 x 95mm x Rounded 4
- 82 x 82mm x 1.200m Rounded 4
- 82 x 82mm x 1.250m Chamfered & Bead
- 82 x 82mm x 1.200m Chamfered

Components (Softwood Decking)

- 82 x 82mm x 1.200m Traditional Cap
- 41 x 41mm x 900mm Rounded 4 Corners
- 41 x 41mm x 895mm Turned
- 41 x 41mm x 895mm Chamfered

ENVIRONMENTAL CREDENTIALS

Certification

PEFC
FSC

Origin

Finland, Sweden, Denmark and Norway

TECHNICAL INFORMATION

Physical Structure

Strong and moderately hard

Durability

AC500 vacuum pressure treatment and to user class 3 minimum 15 year desired life

Moisture Content

16-18%

Working Qualities

Capable of a smooth clean finish, stains and varnishes well

Supplied Finish

Machined to profile

Storage Advice

Under Cover