

## OH Doors & Panels



## Further Product Information

### DIMENSIONS

#### Sandwich Panels

- 28 x 1200 x 2400 Chen Chen
- 45 x 1030 x 2250 Oak
- 45 x 1030 x 2250 Sapele
- Tricoya/Medite Exterior

#### Door Blanks

- 58 x 935 x 2150 Engineered Exterior Blank
- 44 x 935 x 2150 CW Engineered Exterior Door Blank

### ENVIRONMENTAL CREDENTIALS

#### Certification

FSC

#### Origin

Central, Western & East Africa, Denmark

### TECHNICAL INFORMATION

#### Species

Oak, Sapele & Chen Chen

#### Storage and Handling

Laminated solid timber panels should be stored on a flat and level surface in a dry, well-ventilated building. Cover to keep clean and keep out sunlight, but allow air circulation. Handle with clean gloves and do not drag door blanks across one another or across other surfaces. Panels should not be subject to: abnormal heat, extreme dryness, humid conditions or sudden changes therein. They should be conditioned to average prevailing relative humidity of the locality before processing and

hanging. For the best control of humidity to avoid warping and bending the laminated solid timber panels must always be wrapped in plastic. When the panel is unpacked always stack the panel on wood beddings or similar to secure ventilation around the panel.

### **Purchasing Cycle**

Monthly